

Accessories

Lens Options

8177A | 8177B
Hex Cell Louver



9141A | 9141B
Clear Lens



9143A | 9143B
Frosted Lens



9153A | 9153B
Anti UV Filter



9155A | 9155B
Linear Spread Lens



9156A | 9156B
Prismatic Spread Lens



9157A | 9157B
Solite Lens



9199A | 9199B
Frosted Borosilicate Lens



Bevel Trim Lens Options

B
Borosilicate Lens



C
Clear Lens



F
Frosted Lens



L
Linear Spread Lens



P
Prismatic Lens



S
Solite Lens



U
Anti UV Filter



Mounting Options

CB27
(2) 27" C-Channel Bars



CB52
(2) 52" C-Channel Bars

NB
(2) Nailer Bars extendable from 14"-24"
Ships with all housings



Lamps MHMR16



LM16-203012
20W LAMP GE
MHMR16 3000K 12°
Spot

LM16-203025
20W LAMP GE
MHMR16 3000K 25°
Flood

LM16-203040
20W LAMP GE
MHMR16 3000K 40°
Wide Flood

LM16-393012
39W LAMP GE
MHMR16 3000K 12°
Spot

LM16-393025
39W LAMP GE
MHMR16 3000K 25°
Flood

LM16-393040
39W LAMP GE
MHMR16 3000K 40°
Wide Flood

LM16-394012
39W LAMP GE
MHMR16 4000K 12°
Spot

LM16-394025
39W LAMP GE
MHMR16 4000K 25°
Flood

LM16-394040
39W LAMP GE
MHMR16 4000K 40°
Wide Flood

ER
Emergency Relay Module — Remotely mounted module enables Low Voltage fixtures to switch to an emergency backup power supply (by others). Works with input voltages of 120-277V, 100W maximum.

Trimless Adapter
325CCR - Sliver 3³/₄" Ø Round Trims
325CCS - Sliver 3³/₄" Square Trims