


Wall Wash



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum with torsion spring mounting.
 Housing: All-Ways Square™ housing allows alignment of square aperture (up to 45° rotation) after housing installation and prior to finish ceiling installation. Patent pending. Fabricated of 20 ga. galvanized steel with thru wire J-box, 2 in 2 out (4 in 4 out for IC/Airtight) at min. 90°C, #12 AGW thru branch circuit wiring. Housing and trim supplied as one complete unit.
 Trim Lens: MultiTex proprietary molded low iron lens.

LAMP: (not included)

(1) 20W or 39W MHMR16 GX10.

MOUNTING:

Butterfly brackets and adjustable nailer bars with integral nails provided. Nailer bars are extendible from 14" to 24" centers.

VOLTAGE:

Specify 120V or 277V.

BALLAST:

Solid state electronic.

Note: Due to ballast / dimmer match some dimmers may cause ballast hum. Check with dimmer manufacturer for suitability.

CEILING CUT OUT:

3 1/2" x 3 1/2"

NOTES:

- Housing included with trim.
- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 1 lens option.
- Not for use with ES16 lamps.



MultiTex™

Glass lens with five different surface textures for maximum uniformity.

LISTINGS:

Dry/damp/wet under covered ceiling.



IC/Airtight housing meets Washington state airflow requirement and ASTM E283. Chicago Plenum housing is Chicago Plenum rated. IBEW union made.

PHOTOMETRICS:

Distance From Ceiling in Feet	3' on center 3' from wall					
	0.5	2.7	2.6	2.6	2.7	2.6
1.5	10.5	9.3	9.3	10.5	9.1	9.1
2.5	24.2	22.8	22.8	24.2	22.5	22.5
3.5	31.5	30.6	30.7	31.5	30.2	30.2
4.5	33.7	32.6	32.7	33.7	32.0	32.0
5.5	30.4	30.3	30.3	30.4	29.3	29.3
6.5	25.7	25.9	26.0	25.7	24.8	24.8
7.5	22.0	22.4	22.4	22.1	21.2	21.2


Lamp: 39W MHMR16 GX10, FL40, 2100 Lumens
 Reflectances: 0.8, 0.5, 0.2
 LLF: 0.8
 Mounting Height: 8 FT

HOUSING INFORMATION

New Construction

BL718-A (20W)


BL170-A (39W)



IC/Airtight

BL718-A-IC (20W)


(Not available in 39W)



Chicago Plenum

BL718-A-CP (20W)

BL170-A-CP (39W)



ORDERING INFORMATION

Trim	– Finish	– Housing	– Voltage	– Accessories
1658	10 - White	20W MHMR16	120V	CB27 - 27" C-Channel Bars
Bevel Trim	21 - Black	BL718-A - New Construction	277V	CB52 - 52" C-Channel Bars
Wall Wash,	28 - Metalized Grey	BL718-A-IC - IC/Airtight		LAMPS - MHMR16 20W / 39W
New Construction and		BL718-A-CP - Chicago Plenum		
Chicago Plenum:		39W MHMR16		
20W or 39W MHMR16		BL170-A - New Construction		
IC/Airtight: 20W MHMR16		BL170-A-CP - Chicago Plenum		

How to Specify	1658	–	–	–	–
Trim	– Finish	– Housing	– Voltage	– Accessories	