


Wall Wash



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum with torsion spring mounting.
 Housing: All-Ways Square™ housing allows alignment of square aperture (up to 45° rotation) after housing installation and prior to finish ceiling installation. Patent pending. Fabricated of 20 ga. galvanized steel with thru wire J-box, 2 in 2 out (4 in 4 out for IC/ Airtight) at min. 90°C, #12 AGW thru branch circuit wiring. Housing and trim supplied as one complete unit.
 Trim Lens: MultiTex proprietary molded low iron lens.

LAMP: (not included)

(1) 20W or 39W MHMR16 GX10.

MOUNTING:

Butterfly brackets and adjustable nailer bars with integral nails provided. Nailer bars are extendible from 14" to 24" centers.

VOLTAGE:

Specify 120V or 277V.

BALLAST:

Solid state electronic.

Note: Due to ballast / dimmer match some dimmers may cause ballast hum. Check with dimmer manufacturer for suitability.

CEILING CUT OUT:

3 1/2" x 3 1/2"

NOTES:

- Housing included with trim.
- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 1 lens option.
- Not for use with ES16 lamps.



MultiTex™

Glass lens with five different surface textures for maximum uniformity.

LISTINGS:

Dry/damp/wet under covered ceiling.



IC/Airtight housing meets Washington state airflow requirement and ASTM E283. Chicago Plenum housing is Chicago Plenum rated. IBEW union made.

PHOTOMETRICS:

Distance From Ceiling in Feet	3' on center 3' from wall					
	0.5	2.7	2.6	2.6	2.7	2.6
1.5	10.5	9.3	9.3	10.5	9.1	9.1
2.5	24.2	22.8	22.8	24.2	22.5	22.5
3.5	31.5	30.6	30.7	31.5	30.2	30.2
4.5	33.7	32.6	32.7	33.7	32.0	32.0
5.5	30.4	30.3	30.3	30.4	29.3	29.3
6.5	25.7	25.9	26.0	25.7	24.8	24.8
7.5	22.0	22.4	22.4	22.1	21.2	21.2


Lamp: 39W MHMR16 GX10, FL40, 2100 Lumens
 Reflectances: 0.8, 0.5, 0.2
 LLF: 0.8
 Mounting Height: 8 FT

HOUSING INFORMATION

New Construction

BL718-A (20W)


BL170-A (39W)



IC/Airtight

BL718-A-IC (20W)


(Not available in 39W)



Chicago Plenum

BL718-A-CP (20W)

BL170-A-CP (39W)



HOW TO SPECIFY

Trim	Finish	Housing	Voltage	Accessories
1650				
1658 Bevel Trim Wall Wash, New Construction and Chicago Plenum: 20W or 39W MHMR16 IC/Airtight: 20W MHMR16	10 - White 21 - Black 28 - Metalized Grey	20W MHMR16 BL718-A - New Construction BL718-A-IC - IC/Airtight BL718-A-CP - Chicago Plenum 39W MHMR16 BL170-A - New Construction BL170-A-CP - Chicago Plenum	120V 277V	CB27 - 27" C-Channel Bars CB52 - 52" C-Channel Bars LAMPS - MHMR16 20W / 39W