



BEVEL® Trimless Metal Halide

2666

Wall Wash



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum with torsion spring mounting.
 Housing: All-Ways Square™ housing allows alignment of rectangular aperture (up to 30° rotation) after housing installation and prior to finish ceiling installation. Patent pending. Fabricated of 20 ga. galvanized steel with thru wire J-box, 4 in 4 out at min. 90°C, #12 AGW thru branch circuit wiring.
 Housing and trim supplied as one complete unit.
 Trim Lens: MultiTex proprietary molded low iron lens.

LAMP: (not included)

(2) 20W or 39W MHMR16 GX10.

MOUNTING:

Butterfly brackets and adjustable nailer bars with integral nails provided. Nailer bars are extendible from 14" to 24" centers.

VOLTAGE:

Specify 120V or 277V.

BALLAST:

Solid state electronic.

Note: Due to ballast / dimmer match some dimmers may cause ballast hum. Check with dimmer manufacturer for suitability.

CEILING CUT OUT:

New Construction	5 1/16" x 3 1/2"
Mill Work	5 3/8" x 3 5/16"

NOTES:

- Housing included with trim.
- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- For drywall installation only.
- Not for use with acoustical ceilings.
- Maximum Millwork thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 1 lens option.
- Not for use with ES16 lamps

LISTINGS:

Dry/damp location.




IBEW union made.

PHOTOMETRICS:

Distance From Ceiling in Feet	3' on center 3' from wall					
	0.5	8.8	8.6	8.1	8.6	8.9
1.5	23.5	23.4	22.5	23.4	23.5	
2.5	46.0	46.1	45.5	46.2	46.0	
3.5	62.3	63.0	62.8	63.0	62.3	
4.5	66.0	67.0	66.9	66.9	65.8	
5.5	61.5	62.5	62.5	62.6	61.6	
6.5	53.4	54.3	54.3	54.3	53.5	
7.5	44.0	44.9	44.8	44.7	44.1	

Lamp: (2) 39W MHMR16 GX10, FL40, 2100 Lumens
 Reflectances: 0.8, 0.5, 0.2 LLF: 0.8
 Mounting Height: 8 FT 69.4% Efficiency




HOUSING INFORMATION

New Construction

FL928-A (20W)


FL480-A (39W)



Millwork

FL928-A-ML (20W)

FL480-A-ML (39W)



HOW TO SPECIFY

Trim	Finish	Trim Lens*	Housing	Voltage	Accessories
1624		*Frosted is standard unless option is specified			
2666 Bevel Trimless Wall Wash, (2) 20W or 39W MHMR16	10 - White 21 - Black 28 - Metalized Grey RAL - Special Color	B - Borosilicate Clear Lens C - Clear Lens F - Frosted Lens L - Linear Spread Lens P - Prismatic Lens S - Solite U - Anti UV Filter	20W MHMR16 FL928-A - New Construction FL928-A-ML-XX - Millwork XX=Specify Color (10, 21, 28, RAL) 39W MHMR16 FL480-A - New Construction FL480-A-ML-XX - Millwork XX=Specify Color	120V 277V	CB27 - 27" C-Channel Bars CB52 - 52" C-Channel Bars ACCESSORY HOLDER - Consult Factory LAMPS - MHMR16 20W / 39W