



# BEVEL® Trimless Metal Halide

# 2666

## Wall Wash



### LUMINAIRE INFORMATION

#### APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

#### MATERIALS:

Trim: Die cast aluminum with torsion spring mounting.  
 Housing: All-Ways Square™ housing allows alignment of rectangular aperture (up to 30° rotation) after housing installation and prior to finish ceiling installation. Patent pending. Fabricated of 20 ga. galvanized steel with thru wire J-box, 4 in 4 out at min. 90°C, #12 AGW thru branch circuit wiring.  
 Housing and trim supplied as one complete unit.  
 Trim Lens: MultiTex proprietary molded low iron lens.

#### LAMP: (not included)

(2) 20W or 39W MHMR16 GX10.

#### MOUNTING:

Butterfly brackets and adjustable nailer bars with integral nails provided. Nailer bars are extendible from 14" to 24" centers.

#### VOLTAGE:

Specify 120V or 277V.

#### BALLAST:

Solid state electronic.

Note: Due to ballast / dimmer match some dimmers may cause ballast hum. Check with dimmer manufacturer for suitability.

#### CEILING CUT OUT:

3 1/2" x 5 11/16"

#### NOTES:

- Housing included with trim.
- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- For drywall installation only.
- Not for use with acoustical ceilings.
- Maximum Millwork thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 1 lens option.
- Not for use with ES16 lamps

#### LISTINGS:

Dry/damp location.



IBEW union made.

#### PHOTOMETRICS:

Distance From Ceiling in Feet	3' on center 3' from wall					
	0.5	8.8	8.6	8.1	8.6	8.9
1.5	23.5	23.4	22.5	23.4	23.5	
2.5	46.0	46.1	45.5	46.2	46.0	
3.5	62.3	63.0	62.8	63.0	62.3	
4.5	66.0	67.0	66.9	66.9	65.8	
5.5	61.5	62.5	62.5	62.6	61.6	
6.5	53.4	54.3	54.3	54.3	53.5	
7.5	44.0	44.9	44.8	44.7	44.1	

Lamp: (2) 39W MHMR16 GX10, FL40, 2100 Lumens  
 Reflectances: 0.8, 0.5, 0.2 LLF: 0.8  
 Mounting Height: 8 FT 69.4% Efficiency



#### MultiTex™


Glass lens with five different surface textures for maximum uniformity.

### HOUSING INFORMATION

#### New Construction

**FL928-A** (20W)


**FL480-A** (39W)



#### Millwork

**FL928-A-ML** (20W)

**FL480-A-ML** (39W)



### ORDERING INFORMATION

Trim	Finish	Housing	Voltage	Accessories
<b>2666</b>	<b>10</b> - White	<b>20W MHMR16</b>	<b>120V</b>	<b>CB27</b> - 27" C-Channel Bars
Bevel Trimless	<b>21</b> - Black	<b>FL928-A</b> - New Construction	<b>277V</b>	<b>CB52</b> - 52" C-Channel Bars
Wall Wash,	<b>28</b> - Metalized Grey	<b>FL928-A-ML</b> - Millwork		<b>ACCESSORY HOLDER</b> -
(2) 20W or 39W MHMR16		39W MHMR16		Consult Factory
		<b>FL480-A</b> - New Construction		
		<b>FL480-A-ML</b> - Millwork		

How to Specify	2666	Finish	Housing	Voltage	Accessories
	Trim	Finish	Housing	Voltage	Accessories



USA Illumination™  
 www.usaillumination.com  
 info@usaillumination.com

1126 River Road  
 New Windsor, NY 12553

T 845-565-8500  
 F 845-561-1130

©2009, USAI, LLC.  
 All rights reserved.  
 All designs protected by copyright.  
 Rev. 11/16/09