


Sliver Low Voltage Halogen

Wall Wash

5898 5899



For trimless application use 75TWLR housing

LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum / steel. Torsion spring mounting.

5898 - Vertical Groove Black Baffle

5899 - White Cone

Lens: MultiTex proprietary molded low-iron lens.

LAMP: (not included) When using IR lamps, 37W Max. Must use 25° lamp for optimum wall wash performance. (1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory). Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4 3/8" Ø

LISTINGS:

Dry/damp location.



IC/Airtight housing meets Washington state airflow requirement and ASTM E283. Chicago Plenum housing is Chicago Plenum rated. IBEW union made.


NOTES:

- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- No lens options available.
- Trimless available for 75W New Construction only.*



MultiTex™
Glass lens with five different surface textures for maximum uniformity.

PHOTOMETRICS:



Distance From Ceiling in Feet	3' on center 2.5' from wall					
	0.5	4.0	3.9	3.6	3.9	4.0
1.5	12.0	12.0	10.8	12.0	12.0	12.0
2.5	25.4	25.5	23.5	25.5	25.5	25.5
3.5	32.1	32.2	30.8	32.2	32.2	32.2
4.5	28.2	28.5	28.1	28.5	28.1	28.1
5.5	21.8	22.1	22.1	22.2	21.8	21.8
6.5	16.8	17.1	17.1	17.1	16.9	16.9
7.5	13.0	13.2	13.2	13.2	13.0	13.0

Lamp: 75W MR16 GU5.3 40°, 1326 Lumens
Reflectances: 0.8, 0.5, 0.2, LLF: 0.8, Mounting Height: 8 FT
69.1% Efficiency

HOUSING INFORMATION

New Construction 50TW - (50W)	New Construction 75TW - (75W)	New Construction for Trimless 75TWLR - (75W)*	IC/Airtight 50ICN - (50W)	Chicago Plenum 50TWCP - (50W)	Remote Transformer 50RM - (50W)
14 3/4"	15 1/2"	15 1/2"	17 7/8"	15 1/2"	14 3/4"

HOW TO SPECIFY

Trim	Finish	Housing	Voltage	Accessories
<p>5898 - Vertical Groove Black Baffle</p> <p>5899 - White Cone</p> <p>Sliver Wall Wash, 75W Max. MR16 GU5.3</p>	<p>10 - White</p> <p>12 - Brushed Stainless Steel</p> <p>21 - Black</p> <p>22 - Textured White</p> <p>28 - Metalized Grey</p>	<p>50TW - New Construction</p> <p>75TW - New Construction</p> <p>75TWLR - New Construction for Trimless</p> <p>50ICN - IC/Airtight</p> <p>50TWCP - Chicago Plenum</p> <p>50RM - Remote Transformer</p>	<p>120V</p> <p>277V</p>	<p>ER - Emergency Relay</p>