


Sliver Low Voltage Halogen

Shallow Regress Downlight

7862



For trimless application use 75TWLR housing

LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum / steel. Torsion spring mounting.
Lens: Clear.

LAMP: (not included) When using IR lamps, 37W Max.
(1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).
Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4 3/8" Ø

LISTINGS:

Dry/damp/wet under cover ceiling.




IC/Airtight housing meets Washington state airflow requirement and ASTM E283.
Chicago Plenum housing is Chicago Plenum rated.
IBEW union made.

NOTES:

- Maximum ceiling thickness 1 inch.
Consult factory for other ceiling conditions.
- Maximum 2 lens options (size B).
- Trimless available for 75W New Construction only.*

PHOTOMETRICS:



Bare lamp photometrics
75W MR16 GU5.3 36°
Clear lens

Ft below	FC nadir	Dia. @ 50%
6.0	70.2	5.2
8.0	39.5	6.2
10.0	25.2	7.3
12.0	17.5	8.3
14.0	12.9	9.4
16.0	9.8	10.4

HOUSING INFORMATION

New Construction 50TW - (50W)	New Construction 75TW - (75W)	New Construction for Trimless 75TWLR - (75W)*	IC/Airtight 50ICN - (50W)	Chicago Plenum 50TWCP - (50W)	Remote Transformer 50RM - (50W)	Retrofit 100 - (50W)
4"	4"	3 7/8"	7 7/16"	4"	4"	4 13/16"
14 3/4"	15 1/2"	15 1/2"	17 5/8"	15 1/2"	14 3/4"	13 7/8"

HOW TO SPECIFY

