


Sliver Low Voltage Halogen

7867 7869 7872

Downlight



For trimless application use 75TWLR housing

LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum / steel. Torsion spring mounting.
Lens: Clear.

LAMP: (not included) When using IR lamps, 37W Max.
(1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).
Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4 3/8" Ø

LISTINGS:

Dry/damp/wet under cover ceiling.




IC/Airtight housing meets Washington state airflow requirement and ASTM E283.
Chicago Plenum housing is Chicago Plenum rated.
IBEW union made.

NOTES:

- Maximum ceiling thickness 1 inch.
Consult factory for other ceiling conditions.
- Maximum 2 lens options (size B).
- Trimless available for 75W New Construction only.*

PHOTOMETRICS:



LTL No.: 13819.ies
75W MR16 GU5.3 36°
Clear lens
67.8% Efficiency

| Ft below | FC nadir | Dia. @ 50% |
|----------|----------|------------|
| 6.0 | 85.3 | 3.4 |
| 8.0 | 48.0 | 4.6 |
| 10.0 | 30.7 | 5.7 |
| 12.0 | 21.3 | 6.9 |
| 14.0 | 15.7 | 8.0 |
| 16.0 | 12.0 | 9.2 |

HOUSING INFORMATION

| New Construction 50TW - (50W) | New Construction 75TW - (75W) | New Construction for Trimless 75TWLR - (75W)* | IC/Airtight 50ICN - (50W) | Chicago Plenum 50TWCP - (50W) | Remote Transformer 50RM - (50W) | Retrofit 100 - (50W) |
|----------------------------------|----------------------------------|--|------------------------------|----------------------------------|------------------------------------|-------------------------|
| | | | | | | |
| 14 3/4" | 15 1/2" | 15 1/2" | 17 5/8" | 15 1/2" | 14 3/4" | 13 5/8" |

HOW TO SPECIFY

| Trim | Finish | Housing | Voltage | Accessories |
|--|---|--|----------------------------|--|
| 7867 - Chrome Cone 7869 - White Cone 7872 - Vertical Groove Black Baffle Sliver Downlight, 75W Max. MR16 GU5.3 | 10 - White 12 - Brushed Stainless Steel 21 - Black 22 - Textured White 28 - Metalized Grey | 50TW - New Construction 75TW - New Construction 75TWLR - New Construction for Trimless 50ICN - IC/Airtight 50TWCP - Chicago Plenum 50RM - Remote Transformer 100 - Retrofit | 120V 277V | 8177B - Hex Cell Louver 9143B - Frosted Lens 9153B - Anti UV Filter 9155B - Linear Spread Lens 9156B - Prismatic Spread Lens 9157B - Solite Lens 9199B - Frosted Borosilicate Lens ER - Emergency Relay |