


# Sliver Low Voltage Halogen

# 7882

## Adjustable 45°



For trimless application use 75TWLR housing

### LUMINAIRE INFORMATION

#### APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

#### MATERIALS:

Trim: Die cast aluminum / steel. Torsion spring mounting.  
Lens: Clear.

**LAMP:** (not included) When using IR lamps, 37W Max.  
(1) 75W Max. MR16 GU5.3.

#### TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).  
Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

#### ADJUSTMENT:

360° horizontal and 45° vertical tilt.

#### VOLTAGE:

Specify 120V or 277V.

#### CEILING CUT OUT:

4 3/8" Ø

#### LISTINGS:

Dry/damp/wet under cover ceiling.




IC/Airtight housing meets Washington state airflow requirement and ASTM E283.  
Chicago Plenum housing is Chicago Plenum rated.  
IBEW union made.

#### NOTES:

- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 2 lens options (size B).
- Trimless available for 75W New Construction only.\*

#### PHOTOMETRICS:



LTL No.: 13925.ies  
75W MR16 GU5.3 36° (tilted 45°), Clear lens  
54.8% Efficiency

### HOUSING INFORMATION

New Construction 50TW - (50W)	New Construction 75TW - (75W)	New Construction for Trimless 75TWLR - (75W)*	IC/Airtight 50ICN - (50W)	Chicago Plenum 50TWCP - (50W)	Remote Transformer 50RM - (50W)

### HOW TO SPECIFY

Trim	Finish	Housing	Voltage	Accessories
7882				
<b>7882</b> Sliver Adjustable 45°, 75W Max. MR16 GU5.3	10 - White 12 - Brushed Stainless Steel 21 - Black 22 - Textured White 28 - Metalized Grey	50TW - New Construction 75TW - New Construction 75TWLR - New Construction for Trimless 50ICN - IC/Airtight 50TWCP - Chicago Plenum 50RM - Remote Transformer	120V 277V	8177B - Hex Cell Louver 9143B - Frosted Lens 9153B - Anti UV Filter 9155B - Linear Spread Lens 9156B - Prismatic Spread Lens 9157B - Solite Lens 9199B - Frosted Borosilicate Lens ER - Emergency Relay