


Sliver Low Voltage Halogen

Adjustable 45°

7927 7937 7985



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum / steel. Torsion spring mounting.
Lens: Clear.

LAMP: (not included) When using IR lamps, 37W Max.
(1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).
Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

ADJUSTMENT:

360° horizontal rotation in 90° increments and 45° vertical tilt.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4 3/8" Ø

LISTINGS:

Dry/damp location.




IC/Airtight housing meets Washington state airflow requirement and ASTM E283.
Chicago Plenum housing is Chicago Plenum rated.
IBEW union made.

NOTES:

- Maximum ceiling thickness 1 inch.
Consult factory for other ceiling conditions.
- Maximum 2 lens options (size A).
- Trimless available for 75W New Construction only.*

PHOTOMETRICS:

Distribution chart



LTL No.: 13820.ies
75W MR16 GU5.3 36°
(tilted 45°)
Clear lens

HOUSING INFORMATION

New Construction
50TW - (50W)












New Construction
75TW - (75W)

New Construction
for Trimless
75TWLS - (75W)*

IC/Airtight
50ICN - (50W)

Chicago Plenum
50TWCP - (50W)

Remote Transformer
50RM - (50W)



14 3/4"

15 1/2"

15 1/2"

17 7/8"

15 1/2"

14 3/4"

HOW TO SPECIFY

Trim	Finish	Housing	Voltage	Accessories
<p>7927 - Chrome Cone 7937 - White Cone 7985 - Vertical Groove Black Baffle Sliver Adjustable 45°, 75W Max. MR16 GU5.3</p>	<p>10 - White 12 - Brushed Stainless Steel 21 - Black 22 - Textured White 28 - Metalized Grey</p>	<p>50TW - New Construction 75TW - New Construction 75TWLS - New Construction for Trimless 50ICN - IC/Airtight 50TWCP - Chicago Plenum 50RM - Remote Transformer</p>	<p>120V 277V</p>	<p>8177A - Hex Cell Louver 9143A - Frosted Lens 9153A - Anti UV Filter 9155A - Linear Spread Lens 9156A - Prismatic Spread Lens 9157A - Solite Lens 9199A - Frosted Borosilicate Lens ER - Emergency Relay</p>