


Sliver Low Voltage Halogen

7967 7969 7972

Downlight



For trimless application use 75TWLS housing

LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum / steel. Torsion spring mounting.
Lens: Clear.

LAMP: (not included)

(1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).
Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4^{3/8}" Ø

LISTINGS:

Dry/damp/wet under cover ceiling.




IC/Airtight housing meets Washington state airflow requirement and ASTM E283.
Chicago Plenum housing is Chicago Plenum rated.
IBEW union made.

NOTES:

- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 2 lens options (size B).
- Trimless available for 75W New Construction only.*

PHOTOMETRICS:

Distribution chart



LTL No.: 13819.ies
75W MR16 GU5.3 36°
Clear lens
67.8% Efficiency

Ft below	FC nadir	Dia. @ 50%
6.0	85.3	3.4
8.0	48.0	4.6
10.0	30.7	5.7
12.0	21.3	6.9
14.0	15.7	8.0
16.0	12.0	9.2

HOUSING INFORMATION

New Construction 50TW - (50W)	New Construction 75TW - (75W)	New Construction for Trimless 75TWLS - (75W)*	IC/Airtight 50ICN - (50W)	Chicago Plenum 50TWCP - (50W)	Remote Transformer 50RM - (50W)	Retrofit 100 - (50W)
4"	4"	3 ^{7/8} "	7 ^{7/16} "	4"	4"	4 ^{13/16} "
14 ^{3/4} "	15 ^{1/2} "	15 ^{1/2} "	12"	15 ^{1/2} "	14 ^{3/4} "	13 ^{7/8} "

ORDERING INFORMATION

Trim	Finish	Housing	Voltage	Accessories
7967 - Chrome Cone	10 - White	50TW - New Construction	120V	8177B - Hex Cell Louver
7969 - White Cone	12 - Brushed Stainless Steel	75TW - New Construction	277V	9143B - Frosted Lens
7972 - Vertical Groove Black Baffle	21 - Black	75TWLS - New Construction for Trimless		9153B - Anti UV Filter
	22 - Textured White	50ICN - IC/Airtight		9155B - Linear Spread Lens
	28 - Metalized Grey	50TWCP - Chicago Plenum		9156B - Prismatic Spread Lens
Sliver		50RM - Remote Transformer		9157B - Solite Lens
Downlight,		100 - Retrofit		9199B - Frosted Borosilicate Lens
75W Max. MR16 GU5.3				ER - Emergency Relay

How to Specify

Trim - Finish - Housing - Voltage - Accessories



USA Illumination™
www.usaillumination.com
info@usaillumination.com

1126 River Road
New Windsor, NY 12553

T 845-565-8500
F 845-561-1130

© 2009, USAI, LLC.
All rights reserved.
All designs protected by copyright.