


Stellos Low Voltage Halogen

9354 9357 9358 9359

Downlight



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum. Torsion spring mounting.

9354 - Vertical Groove Black Baffle

9357 - Chrome Cone

9358 - Black Cone

9359 - White Cone

Lens: Clear.

LAMP: (not included) When using IR lamps, 37W Max. (1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).

Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4³/₈" Ø

LISTINGS:

Dry/damp/wet under cover ceiling.




IC/Airtight housing meets Washington state airflow requirement and ASTM E283.

Chicago Plenum housing is Chicago Plenum rated. IBEW union made.

NOTES:

- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 2 lens options (size B).

PHOTOMETRICS:



LTL No.: 14456.ies
75W MR16 GU5.3 40°
Clear lens
67.8% Efficiency

Ft	FC	Dia.
below	nadir	@ 50%
6.0	51.4	3.4
8.0	28.9	4.6
10.0	18.5	5.7
12.0	12.9	6.9
14.0	9.4	8.0
16.0	7.2	9.2

HOUSING INFORMATION

New Construction
50TW - (50W)













New Construction
75TW - (75W)

IC/Airtight
50ICN - (50W)

Chicago Plenum
50TWCP - (50W)

Remote Transformer
50RM - (50W)

Retrofit
100 - (50W)



14³/₄"

15¹/₂"

17⁵/₈"

15¹/₂"

14³/₄"

13⁷/₈"

ORDERING INFORMATION

Trim	– Finish	– Housing	– Voltage	– Accessories
9354 - Vertical Groove Black Baffle	10 - White	50TW - New Construction	120V	8177B - Hex Cell Louver
9357 - Chrome Cone	21 - Black	75TW - New Construction	277V	9143B - Frosted Lens
9358 - Black Cone	28 - Metalized Grey	50ICN - IC/Airtight		9153B - Anti UV Filter
9359 - White Cone		50TWCP - Chicago Plenum		9155B - Linear Spread Lens
Stellos		50RM - Remote Transformer		9156B - Prismatic Spread Lens
Downlight,		100 - Retrofit		9157B - Solite Lens
75W Max. MR16 GU5.3				9199B - Frosted Borosilicate Lens
				ER - Emergency Relay

How to Specify

Trim – Finish – Housing – Voltage – Accessories

USAI®

USA Illumination™
www.usaillumination.com
info@usaillumination.com

1126 River Road
New Windsor, NY 12553

T 845-565-8500
F 845-561-1130

©2009, USAI, LLC.
All rights reserved.
All designs protected by copyright.
09/02/2010