


BEVEL® Low Voltage Halogen

9363

Adjustable 35°



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum with torsion spring mounting.
 Housing: All-Ways Square™ housing allows alignment of square aperture (up to 45° rotation) after housing installation and prior to finish ceiling installation. Patent pending. Fabricated of 20 ga. galvanized steel with thru wire J-box, 2 in 2 out (4 in 4 out for IC/Airtight) at min. 90°C, #12 AGW thru branch circuit wiring. Housing and trim supplied as one complete unit.
 Trim Lens: Frosted

LAMP: (not included) When using IR lamps, 37W Max.
 New Construction / Chicago Plenum: (1) 71W max. MR16 GU5.3
 IC/Airtight: (1) 50W max. MR16 GU5.3

ADJUSTMENT:

362° lockable horizontal rotation and 35° lockable vertical tilt.

MOUNTING:

Butterfly brackets and adjustable nailer bars with integral nails provided. Nailer bars are extendible from 14" to 24" centers.

VOLTAGE:

Specify 120V, 277V or 347V.
 347V is for New Construction housing only.

TRANSFORMER:

Low voltage magnetic toroidal HPF. Low voltage solid state electronic optionally available (consult factory).
 Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

CEILING CUT OUT:

3 1/2" x 3 1/2"

LISTINGS:

Dry/damp/wet under covered ceiling.




IC/Airtight housing meets Washington state airflow requirement and ASTM E283. Chicago Plenum housing is Chicago Plenum rated. IBEW union made.

NOTES:

- Housing included with trim.
- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 1 lens option.

PHOTOMETRICS:

Distribution chart




LTL No.: 13924.ies
 71W MR16 GU5.3 40° (tilted 35°)
 Frosted lens - 46.3% Efficiency
 Solite lens - 53.2% Efficiency

HOUSING INFORMATION


New Construction - (71W)

BL101-A




IC/Airtight - (50W)

BL101-A-IC



Chicago Plenum - (71W)

BL101-A-CP



HOW TO SPECIFY

Trim	Finish	Trim Lens*	Housing	Voltage	Accessories
9363		*Frosted is standard unless option is specified			
9363 Bevel Trim Adjustable 35°, New Construction and Chicago Plenum: 71W MR16 GU5.3 IC/Airtight: 50W MR16 GU5.3	10 - White 21 - Black 28 - Metalized Grey	B - Borosilicate Clear Lens C - Clear Lens F - Frosted Lens L - Linear Spread Lens P - Prismatic Lens S - Solite U - Anti UV Filter	BL101-A - New Construction BL101-A-IC - IC/Airtight BL101-A-CP - Chicago Plenum	120V 277V 347V*	CB27 - 27" C-Channel Bars CB52 - 52" C-Channel Bars ER - Emergency Relay ACCESSORY HOLDER - Consult Factory
				*347V for New Construction housing only.	