


SOLARIS Compact Fluorescent

Downlight



9411 9412 9413 9415 9416



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

- Trim: Die cast aluminum.
- Housing: Fabricated of 20 ga. galvanized steel with external thru wire J-box, 4 in 4 out at min. 90°C, #12 AGW thru branch circuit wiring.
- Housing and trim supplied as one complete unit.
- Reflector: Specular precision molded polycarbonate.
- Suspended Glass: (Specify)
 - SL - Soda Lime
 - BO - Borosilicate
- Glass Finish: (Specify)
 - AC - All Clear
 - AF - All Frosted
 - CC - Clear Center
 - FC - Frosted Center

LAMP: (not included)

- 9411 - (1) 18W Quad G24q-2
- 9412 - (1) 26W Quad G24q-3
- 9413 - (1) 26W / 32W / 42W Triple G24q-4
- 9415 - (2) 18W Quad G24q-2
- 9416 - (2) 26W Quad G24q-3

MOUNTING:

Butterfly brackets and adjustable nailer bars with integral nails provided. Nailer bars are extendible from 14" to 24" centers.

VOLTAGE:

Specify 120V, 277V or 347V.

BALLAST:

Solid state electronic.
 Note: Due to ballast / dimmer match some dimmers may cause ballast hum. Check with dimmer manufacturer for suitability.

CEILING CUT OUT:

8 3/4" Ø

LISTINGS:

Dry/damp location.




IBEW union made.

NOTES:

- Housing included with trim.
 - Maximum ceiling thickness 1 inch.
- Consult factory for other ceiling conditions.

PHOTOMETRICS:


Distribution chart



LTL No.: 08471.ies
 Trim No.: 9415
 (2) 18W Quad G24q-2
 Frosted center glass
 46.3% Efficiency

HOUSING INFORMATION

New Construction



ORDERING INFORMATION

Trim	– Finish	– Suspended Glass	– Glass Finish	– Voltage	– Accessories
9411 - (1) 18W Quad G24q-2	10 - White	SL - Soda Lime	AC - All Clear	120V	CB27 - 27" C-Channel Bars
9412 - (1) 26W Quad G24q-3	21 - Black	BO - Borosilicate	AF - All Frosted	277V	CB52 - 52" C-Channel Bars
9413 - (1) 26W / 32W / 42W Triple G24q-4	28 - Metalized Grey		CC - Clear Center	347V	DIM - Dimming Ballast (consult factory)
9415 - (2) 18W Quad G24q-2			FC - Frosted Center		EM - Emergency Battery EM is 650 lumens max. Note that housing size may differ. Consult factory.
9416 - (2) 26W Quad G24q-3					

How to Specify

Trim – Finish – Suspended Glass – Glass Finish – Voltage – Accessories



USA Illumination™
 www.usaillumination.com
 info@usaillumination.com

1126 River Road
 New Windsor, NY 12553

T 845-565-8500
 F 845-561-1130

©2009. USAI, LLC.
 All rights reserved.
 All designs protected by copyright.