


Stellos Low Voltage Halogen

Shallow Regress Adjustable 45°

9450



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum. Torsion spring mounting.
Lens: Clear.

LAMP: (not included) When using IR lamps, 37W Max.
(1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).
Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

ADJUSTMENT:

360° horizontal in 90° increments and 45° vertical tilt.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4 3/8" Ø

LISTINGS:

Dry/damp/wet under cover ceiling.




IC/Airtight housing meets Washington state airflow requirement and ASTM E283.
Chicago Plenum housing is Chicago Plenum rated.
IBEW union made.

NOTES:

- Maximum ceiling thickness 1 inch.
Consult factory for other ceiling conditions.
- Maximum 2 lens options (size B).

PHOTOMETRICS:



LTL No.: 13925.ies
75W MR16 GU5.3 36° (tilted 45°)
Clear lens
54.8% Efficiency

HOUSING INFORMATION










New Construction
50TW - (50W)

New Construction
75TW - (75W)

IC/Airtight
50ICN - (50W)

Chicago Plenum
50TWCP - (50W)

Remote Transformer
50RM - (50W)



HOW TO SPECIFY

Trim	Finish	Housing	Voltage	Accessories
9450				
9450 Stellos Shallow Regress Adjustable 45°, 75W Max. MR16 GU5.3	10 - White 21 - Black 28 - Metalized Grey	50TW - New Construction 75TW - New Construction 50ICN - IC/Airtight 50TWCP - Chicago Plenum 50RM - Remote Transformer	120V 277V	8177B - Hex Cell Louver 9143B - Frosted Lens 9153B - Anti UV Filter 9155B - Linear Spread Lens 9156B - Prismatic Spread Lens 9157B - Solite Lens 9199B - Frosted Borosilicate Lens ER - Emergency Relay