


# Stellos Low Voltage Halogen

# 9650

## Adjustable 45°



### LUMINAIRE INFORMATION

#### APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

#### MATERIALS:

Trim: Die cast aluminum. Torsion spring mounting.  
Vertical groove black baffle.  
Lens: Clear.

**LAMP:** (not included) When using IR lamps, 37W Max.  
(1) 75W Max. MR16 GU5.3.

#### TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).  
Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

#### ADJUSTMENT:

360° horizontal in 90° increments and 45° vertical tilt.

#### VOLTAGE:

Specify 120V or 277V.

#### CEILING CUT OUT:

4 3/8" Ø

#### LISTINGS:

Dry/damp location.




IC/Airtight housing meets Washington state airflow requirement and ASTM E283.  
Chicago Plenum housing is Chicago Plenum rated.  
IBEW union made.

#### NOTES:

- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- Maximum 2 lens options (size A).

#### PHOTOMETRICS:



LTL No.: 13824.ies  
75W MR16 GU5.3 36° (tilted 25°)  
Clear lens  
58.2% Efficiency

### HOUSING INFORMATION










New Construction  
**50TW** - (50W)

New Construction  
**75TW** - (75W)

IC/Airtight  
**50ICN** - (50W)

Chicago Plenum  
**50TWCP** - (50W)

Remote Transformer  
**50RM** - (50W)



### HOW TO SPECIFY

Trim	Finish	Housing	Voltage	Accessories
9650				
<b>9650</b> - Vertical Groove Black Baffle Stellos Adjustable 45°, 75W Max. MR16 GU5.3	<b>10</b> - White <b>21</b> - Black <b>28</b> - Metalized Grey	<b>50TW</b> - New Construction <b>75TW</b> - New Construction <b>50ICN</b> - IC/Airtight <b>50TWCP</b> - Chicago Plenum <b>50RM</b> - Remote Transformer	<b>120V</b> <b>277V</b>	<b>8177A</b> - Hex Cell Louver <b>9143A</b> - Frosted Lens <b>9153A</b> - Anti UV Filter <b>9155A</b> - Linear Spread Lens <b>9156A</b> - Prismatic Spread Lens <b>9157A</b> - Solite Lens <b>9199A</b> - Frosted Borosilicate Lens <b>ER</b> - Emergency Relay