


Stellos Low Voltage Halogen

9850

Wall Wash



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum. Torsion spring mounting.

Vertical groove black baffle.

Lens: MultiTex proprietary molded low iron lens

LAMP: (not included) When using IR lamps, 37W Max. Must use 25° lamp for optimum wall wash performance. (1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).

Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4³/₈" Ø

LISTINGS:

Dry/damp wet under cover ceiling location.



IC/Airtight housing meets Washington state airflow requirement and ASTM E283.

Chicago Plenum housing is Chicago Plenum rated.

IBEW union made.

NOTES:

- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- No lens options available.



MultiTex™

Glass lens with five different surface textures for maximum uniformity.

PHOTOMETRICS:

Distance From Ceiling in Feet	3' on center 2.5' from wall					
	0.5	1.5	2.5	3.5	4.5	5.5
0.5	4.0	3.9	3.6	3.9	4.0	12.0
1.5	12.0	12.0	10.8	12.0	12.0	25.5
2.5	25.4	25.5	23.5	25.5	25.5	32.2
3.5	32.1	32.2	30.8	32.2	32.2	28.1
4.5	28.2	28.5	28.1	28.5	28.1	21.8
5.5	21.8	22.1	22.1	22.2	21.8	16.9
6.5	16.8	17.1	17.1	17.1	16.9	13.2
7.5	13.0	13.2	13.2	13.2	13.0	

Lamp: 75W MR16 GU5.3, 36° 1326 Lumens
 Reflectances: 0.8, 0.5, 0.2
 LLF: 0.8
 Mounting Height: 8 FT
 69.1% Efficiency

HOUSING INFORMATION











New Construction
50TW - (50W)

New Construction
75TW - (75W)

IC/Airtight
50ICN - (50W)

Chicago Plenum
50TWCP - (50W)

Remote Transformer
50RM - (50W)



ORDERING INFORMATION

Trim

9850 - Vertical Groove Black Baffle
 Stellos
 Wall Wash,
 75W Max. MR16 GU5.3

– Finish

01 - Polished Chrome
07 - Brushed Aluminum
10 - White
21 - Black
28 - Metalized Grey

– Housing

50TW - New Construction
75TW - New Construction
50ICN - IC/Airtight
50TWCP - Chicago Plenum
50RM - Remote Transformer

– Voltage

120V
277V

– Accessories

ER - Emergency Relay

How to Specify

9850 – _____ – _____ – _____ – _____
 Trim – Finish – Housing – Voltage – Accessories

USAI®

USA Illumination™
 www.usaillumination.com
 info@usaillumination.com

1126 River Road
 New Windsor, NY 12553

T 845-565-8500
 F 845-561-1130

©2009, USAI, LLC.
 All rights reserved.
 All designs protected by copyright.
 09/02/2010