


Stellos Low Voltage Halogen

9998

Wall Wash



LUMINAIRE INFORMATION

APPLICATION:

Accent luminaire for Residential, Commercial, Retail or Hospitality environments.

MATERIALS:

Trim: Die cast aluminum. Torsion spring mounting.
Vertical groove black baffle.
Lens: MultiTex proprietary molded low iron lens

LAMP: (not included) When using IR lamps, 37W Max. Must use 25° lamp for optimum wall wash performance. (1) 75W Max. MR16 GU5.3.

TRANSFORMER:

Magnetic toroidal-HPF. Low voltage solid state electronic optionally available (consult factory).
Note: Due to transformer / dimmer match some dimmers may cause transformer hum. Check with dimmer manufacturer for suitability.

ADJUSTMENT:

360° horizontal rotation in 90° increments.

VOLTAGE:

Specify 120V or 277V.

CEILING CUT OUT:

4³/₈" Ø

LISTINGS:

Dry/damp wet under cover ceiling location.



IC/Airtight housing meets Washington state airflow requirement and ASTM E283.
Chicago Plenum housing is Chicago Plenum rated.
IBEW union made.

NOTES:

- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- No lens options available.



MultiTex™

Glass lens with five different surface textures for maximum uniformity.

PHOTOMETRICS:

| Distance From Ceiling in Feet | 3' on center 2.5' from wall | | | | | |
|-------------------------------|--------------------------------|------|------|------|------|------|
| | 0.5 | 4.0 | 3.9 | 3.6 | 3.9 | 4.0 |
| 1.5 | 12.0 | 12.0 | 10.8 | 12.0 | 12.0 | 12.0 |
| 2.5 | 25.4 | 25.5 | 23.5 | 25.5 | 25.5 | 25.5 |
| 3.5 | 32.1 | 32.2 | 30.8 | 32.2 | 32.2 | 32.2 |
| 4.5 | 28.2 | 28.5 | 28.1 | 28.5 | 28.1 | 28.1 |
| 5.5 | 21.8 | 22.1 | 22.1 | 22.2 | 22.2 | 21.8 |
| 6.5 | 16.8 | 17.1 | 17.1 | 17.1 | 17.1 | 16.9 |
| 7.5 | 13.0 | 13.2 | 13.2 | 13.2 | 13.2 | 13.0 |

Lamp: 75W MR16 GU5.3, 36° 1326 Lumens
Reflectances: 0.8, 0.5, 0.2
LLF: 0.8
Mounting Height: 8 FT
69.1% Efficiency

HOUSING INFORMATION










New Construction
50TW - (50W)

New Construction
75TW - (75W)

IC/Airtight
50ICN - (50W)

Chicago Plenum
50TWCP - (50W)

Remote Transformer
50RM - (50W)



HOW TO SPECIFY

| Trim | Finish | Housing | Voltage | Accessories |
|---|---|---|--------------|----------------------|
| 9998 | | | | |
| 9998 - Vertical Groove Black Baffle Stellos Wall Wash, 75W Max. MR16 GU5.3 | 10 - White 21 - Black 28 - Metalized Grey | 50TW - New Construction 75TW - New Construction 50ICN - IC/Airtight 50TWCP - Chicago Plenum 50RM - Remote Transformer | 120V 277V | ER - Emergency Relay |