


# Bevel Housing Low Voltage

## Retrofit For Bevel Square Downlight Trim 9343



# BL100-A-RT



### HOUSING INFORMATION

#### APPLICATION:

For use with USAI Bevel Square low voltage downlight trim in retrofit applications.

#### MATERIALS:

Housing: Fabricated of 20 ga. galvanized steel integral thru wire J-box, 2 in 2 out at min. 90°C, #12 AGW thru branch circuit wiring.

#### LAMP: (not included)

37W max. MR16 GU5.3.

#### MOUNTING:

Screw driven compression mount system.

#### VOLTAGE:

Specify 120V or 277V.

#### TRANSFORMER:

Low voltage solid state electronic.

Note: Due to transformer / dimmer match some dimmers may cause transformer hum.

Check with dimmer manufacturer for suitability.

#### SOCKET:

Porcelain construction with 18 ga., 250°C SF-2 sleeved leads. Sized for MR16 halogen 12V lamps. Bi-pin base GU5.3.

#### LISTINGS:

Dry/damp/wet for under covered ceiling.



IBEW union made.

#### CEILING CUT OUT:



3 5/8" x 3 5/8"

#### NOTES:

- Maximum ceiling thickness 1 inch. Consult factory for other ceiling conditions.
- 120V not compatible with AFCI circuit.

### DIMENSIONS

Retrofit



### COMPATIBLE TRIM

**BEVEL  
Downlight  
9343**



### HOW TO SPECIFY

